



## QSR AD SPECIFICATIONS

Ad Size	Ad Shape	Trim	Bleed
Full Page	Full Page	8-1/2" x 10-7/8" (8.5" x 10.875")	8-3/4" x 11-1/8" (8.75" x 11.125")
1/2 Page	1/2 Vertical	3-5/8" x 10" (3.625" x 10")	N/A
	1/2 Horizontal	7-1/2" x 4-7/8" (7.5" x 4.875")	N/A
2/3 Page	2/3 Vertical	4-7/8" x 10" (4.875" x 10")	N/A
	2/3 Horizontal	7-1/2" x 6-1/2" (7.5" x 6.5")	N/A
1/3 Page	1/3 Vertical	2-3/8" x 10" (2.375" x 10")	N/A
	1/3 Square	4-7/8" x 4-7/8" (4.875" x 4.875")	N/A
1/6 Page	1/6 Vertical	2-3/8" x 4-7/8" (2.375" x 4.875")	N/A
	1/6 Horizontal	4-7/8" x 2-5/16" (4.875" x 2.312")	N/A
1/12 Page	1/12 Square	2-3/8" x 2-5/16" (2.375" x 2.312")	N/A
ADS PLUS			
1/2 Page	1/2 Page Spread	17" x 5-3/8" (17" x 5.375")	17.25" x 5.625"
Full + 1/3	Full + 1/3 Vertical	8-1/2" x 10-7/8" (8.5" x 10.875") PLUS 2-3/4" x 10-7/8" (2.75" x 10.875")	8-3/4" x 11-1/8" (8.75" x 11.125") PLUS 3" x 11-1/8" (3" x 11.125")
2-Page Spread	2-Page Spread	8-1/2" x 10-7/8" (8.5" x 10.875") (two separate full pages)	8-3/4" x 11-1/8" (8.75" x 11.125")

Please submit ads via the QSR Ad Portal at [ads.wtwhmedia.com](https://ads.wtwhmedia.com).

### LIVE (SAFETY) AND BLEED

Keep all live items (not intended to trim) 1/2" inside trim edges. If an ad is designed to bleed to the edge, an 1/8" bleed is required outside of trim. Please make sure to output the pdf accordingly to include the bleed, as this is generally not the default setting. Two-page spreads must be created as two separate full page PDFs.

### MEDIA

**File format:** Ads must be PDF/X-1a files. **Fonts:** Embed all fonts. All fonts sized 12 points or smaller should be 100% black—NOT built as 4-c black.

**Color space:** CMYK – No RGB, LAB or embedded color profiles (such as ICC profiles). No files with PMS colors will be accepted without prior notification.

Otherwise, all PMS colors MUST be converted to CMYK. **Resolution:** 300 dpi. **Maximum file size:** 100 MB.

Artwork submitted is assumed that color, images, and copy are proofed and correct from client. Any necessary artwork or copy preparation may be billed to advertiser.

### PROOF

Client also has the option to submit a SWOP 3 certified proof via mail, as well. By choosing not to supply a SWOP 3 certified proof, the color reproduction of the ad will be based on industry standard best practices to achieve as accurate color as possible from the supplied digital file. If sending a SWOP certified proof, please contact your Customer Service Representative for details.

### QUESTIONS

For ad production questions, please contact:

Brandy Pinion, Customer Service Representative

Direct: 662-234-5481 Ext 127 • [bpinion@wtwhmedia.com](mailto:bpinion@wtwhmedia.com)

**Printing Process:** Offset, computer-to-plate (CTP)

**Binding Method:** Perfect bound

